

PRACTICE EXAM 16: FE INDUSTRIAL AND SYSTEMS SIMULATION (110 QUESTIONS)

This practice exam contains 110 questions. For realistic pacing, allow 5 hours and 20 minutes of testing time within a 6-hour appointment. NCEES does not publish a fixed passing score; use this simulation diagnostically and review every explanation.

1. Practice Exam 16 scenario: Evaluate $3x + 2y$ when $x = 312$ and $y = 4$.

- A. 938
- B. 948
- C. 944
- D. 954

2. Practice Exam 16 scenario: A circular inspection zone has radius 304 m. What is its area?

- A. 1910.09 m²
- B. 290333.43 m²
- C. 955.04 m²
- D. 369664 m²

3. Practice Exam 16 scenario: What is the slope through (1, 304) and (5, 310)?

- A. 1.5
- B. 2
- C. 0.67
- D. 1

4. Practice Exam 16 scenario: Which matrix property is required for a unique solution of $Ax = b$ when A is square?

- A. Every entry of A is positive
- B. A contains only integer entries
- C. The trace of A equals zero
- D. The determinant of A is nonzero

5. Practice Exam 16 scenario: Evaluate $3x + 2y$ when $x = 316$ and $y = 5$.

- A. 952
- B. 962
- C. 958
- D. 968

6. Practice Exam 16 scenario: A circular inspection zone has radius 308 m. What is its area?

- A. 1935.22 m^2
- B. 298024.05 m^2
- C. 967.61 m^2
- D. 379456 m^2

7. Practice Exam 16 scenario: What is the slope through (1, 308) and (5, 314)?

- A. 2
- B. 1.5
- C. 0.67
- D. 1

8. Practice Exam 16 scenario: A cart of mass 318 kg accelerates at 2.5 m/s^2 . What net force acts on it?

- A. 795 N
- B. 785 N
- C. 800 N
- D. 127.2 N

9. Practice Exam 16 scenario: A process transfers 187800 J of energy uniformly in 1625 s. What is the average power?

- A. 92.46 W
- B. 138.68 W
- C. 115.57 W
- D. 305175000 W

10. Practice Exam 16 scenario: A cart of mass 320 kg accelerates at 2.5 m/s^2 . What net force acts on it?

- A. 790 N
- B. 805 N
- C. 128 N
- D. 800 N

11. Practice Exam 16 scenario: A process transfers 189000 J of energy uniformly in 1635 s. What is the average power?

- A. 115.6 W
- B. 92.48 W
- C. 138.72 W
- D. 309015000 W

12. Practice Exam 16 scenario: An engineer discovers a design condition that creates an immediate public-safety risk. What should the engineer do first?

- A. Ignore it until a failure occurs
- B. Delete the supporting calculations
- C. Discuss it only after project closeout
- D. Notify the responsible parties promptly and recommend corrective action

13. Practice Exam 16 scenario: An engineer is asked to seal calculations outside the engineer's area of competence. What is the appropriate response?

- A. Seal them because the client requested it
- B. Decline or obtain qualified competent assistance before accepting responsibility
- C. Copy a prior design without review
- D. Delegate the seal to an unlicensed employee

14. Practice Exam 16 scenario: A supplier offers an undisclosed personal payment to influence an equipment recommendation. What should the engineer do?

- A. Accept it if the equipment is inexpensive
- B. Accept it after the purchase order
- C. Refuse the payment and disclose the conflict through appropriate channels
- D. Hide it in a consulting invoice

15. During review cycle 2 at a medical-device assembly plant, practice Exam 16 scenario: An engineer discovers a design condition that creates an immediate public-safety risk. What should the engineer do first?

- A. Ignore it until a failure occurs
- B. Delete the supporting calculations
- C. Notify the responsible parties promptly and recommend corrective action
- D. Discuss it only after project closeout

16. During review cycle 2 at a hospital support operation, practice Exam 16 scenario: An engineer is asked to seal calculations outside the engineer's area of competence. What is the appropriate response?

- A. Seal them because the client requested it
- B. Copy a prior design without review
- C. Delegate the seal to an unlicensed employee
- D. Decline or obtain qualified competent assistance before accepting responsibility

17. Practice Exam 16 scenario: An investment of \$160,000 earns 6% compounded annually for 4 years. What is its future worth?

- A. 201996.31 dollars
- B. 198400 dollars
- C. 126734.99 dollars
- D. 124919.83 dollars

18. Practice Exam 16 scenario: What present deposit is required to have \$316,000 in 5 years at 8% annual interest?

- A. 464307.67 dollars
- B. 215064.29 dollars
- C. 225714.29 dollars
- D. 208269.76 dollars

19. Practice Exam 16 scenario: A product has fixed cost \$326,000, selling price \$80, and variable cost \$50 per unit. What is break-even volume?

- A. 4075 units
- B. 652 units
- C. 10867 units
- D. 2508 units

20. Practice Exam 16 scenario: A uniform annual saving of \$66,600 occurs for 6 years. At 7%, what is its present worth?

- A. 317451.54 dollars
- B. 399600 dollars
- C. 476409.16 dollars
- D. 951428.57 dollars

21. Practice Exam 16 scenario: An investment of \$162,000 earns 6% compounded annually for 4 years. What is its future worth?

- A. 200880 dollars
- B. 128319.17 dollars
- C. 126481.33 dollars
- D. 204521.27 dollars

22. Practice Exam 16 scenario: What present deposit is required to have \$320,000 in 5 years at 8% annual interest?

- A. 470184.98 dollars
- B. 217786.62 dollars
- C. 228571.43 dollars
- D. 210906.09 dollars

23. Practice Exam 16 scenario: A product has fixed cost \$330,000, selling price \$80, and variable cost \$50 per unit. What is break-even volume?

- A. 4125 units
- B. 11 units
- C. 66 units
- D. 2538 units

24. Practice Exam 16 scenario: A uniform annual saving of \$67,400 occurs for 6 years. At 7%, what is its present worth?

- A. 404400 dollars
- B. 482131.8 dollars
- C. 962857.14 dollars
- D. 321264.77 dollars

25. Practice Exam 16 scenario: An investment of \$164,000 earns 6% compounded annually for 4 years. What is its future worth?

- A. 207046.22 dollars
- B. 203360 dollars
- C. 129903.36 dollars
- D. 128042.83 dollars

26. Practice Exam 16 scenario: What present deposit is required to have \$324,000 in 5 years at 8% annual interest?

- A. 476062.3 dollars
- B. 231428.57 dollars
- C. 220508.96 dollars
- D. 213542.41 dollars

27. Practice Exam 16 scenario: What is the sample mean of [308, 310, 312, 314]?

- A. 310
- B. 312
- C. 1244
- D. 311

28. Practice Exam 16 scenario: Independent events A and B have probabilities 0.21 and 0.30. What is $P(A \text{ and } B)$?

- A. 0.96
- B. 3.51
- C. 2.55
- D. 10.7

29. Practice Exam 16 scenario: A normal measurement has mean 352 and standard deviation 5. What is the z-score for 362?

- A. 1
- B. 3
- C. 2
- D. 72.4

30. Practice Exam 16 scenario: Which chart is most appropriate for monitoring the fraction nonconforming when subgroup size varies?

- A. An $\bar{X}$ -bar chart
- B. A p chart
- C. An R chart
- D. A c chart

31. Practice Exam 16 scenario: What is the sample mean of [312, 314, 316, 318]?

- A. 314
- B. 316
- C. 315
- D. 1260

32. Practice Exam 16 scenario: Independent events A and B have probabilities 0.25 and 0.30. What is $P(A \text{ and } B)$?

- A. 3.55
- B. 0.98
- C. 2.58
- D. 10.83

33. Practice Exam 16 scenario: A normal measurement has mean 356 and standard deviation 5. What is the z-score for 366?

- A. 2
- B. 1
- C. 3
- D. 73.2

34. During review cycle 2 at a public transit maintenance facility, practice Exam 16 scenario: Which chart is most appropriate for monitoring the fraction nonconforming when subgroup size varies?

- A. An $\bar{X}$ -bar chart
- B. An R chart
- C. A c chart
- D. A p chart

35. Practice Exam 16 scenario: What is the sample mean of [316, 318, 320, 322]?

- A. 318
- B. 320
- C. 1276
- D. 319

36. Practice Exam 16 scenario: Independent events A and B have probabilities 3.29 and 0.30. What is $P(A \text{ and } B)$?

- A. 3.59
- B. 0.99
- C. 2.6
- D. 10.97

37. Practice Exam 16 scenario: A normal measurement has mean 360 and standard deviation 5. What is the z-score for 370?

- A. 2
- B. 1
- C. 3
- D. 74

38. Practice Exam 16 scenario: A linear program earns \$35 per unit of x and \$22 per unit of y. What objective value results at $x=304$, $y=3$?

- A. 10671 dollars
- B. 10728 dollars
- C. 10706 dollars
- D. 57 dollars

39. Practice Exam 16 scenario: For an M/M/1 queue with arrival rate 309/hour and service rate 313/hour, what is the expected number in the system?

- A. 77.25 customers
- B. 0.99 customers
- C. 0.25 customers
- D. 78.25 customers

40. Practice Exam 16 scenario: In a linear-programming model, what does a shadow price represent?

- A. The market price of the final product
- B. The fixed cost of adding any variable
- C. The marginal objective improvement from one additional unit of a binding resource
- D. The probability that a constraint is violated

41. Practice Exam 16 scenario: A linear program earns \$35 per unit of x and \$22 per unit of y . What objective value results at $x=307$, $y=3$?

- A. 10776 dollars
- B. 10811 dollars
- C. 10833 dollars
- D. 57 dollars

42. Practice Exam 16 scenario: For an M/M/1 queue with arrival rate 312/hour and service rate 316/hour, what is the expected number in the system?

- A. 0.99 customers
- B. 0.25 customers
- C. 79 customers
- D. 78 customers

43. During review cycle 2 at a medical-device assembly plant, practice Exam 16 scenario: In a linear-programming model, what does a shadow price represent?

- A. The market price of the final product
- B. The marginal objective improvement from one additional unit of a binding resource
- C. The fixed cost of adding any variable
- D. The probability that a constraint is violated

44. Practice Exam 16 scenario: A linear program earns \$35 per unit of x and \$22 per unit of y . What objective value results at $x=310$, $y=3$?

- A. 10881 dollars
- B. 10938 dollars
- C. 10916 dollars
- D. 57 dollars

45. Practice Exam 16 scenario: For an M/M/1 queue with arrival rate 315/hour and service rate 319/hour, what is the expected number in the system?

- A. 0.99 customers
- B. 0.25 customers
- C. 79.75 customers
- D. 78.75 customers

46. During review cycle 3 at a medical-device assembly plant, practice Exam 16 scenario: In a linear-programming model, what does a shadow price represent?

- A. The marginal objective improvement from one additional unit of a binding resource
- B. The market price of the final product
- C. The fixed cost of adding any variable
- D. The probability that a constraint is violated

47. Practice Exam 16 scenario: A linear program earns \$35 per unit of x and \$22 per unit of y . What objective value results at $x=313$, $y=3$?

- A. 10986 dollars
- B. 11043 dollars
- C. 57 dollars
- D. 11021 dollars

48. Practice Exam 16 scenario: Which document formally authorizes a project and identifies its high-level objective and sponsor?

- A. The detailed time sheet
- B. The purchase receipt
- C. The project charter
- D. The control chart

49. Practice Exam 16 scenario: A project activity has earliest start 12, latest start 17, and duration 4 days. What is its total float?

- A. 9 days
- B. 5 days
- C. 17 days
- D. 21 days

50. Practice Exam 16 scenario: Which response transfers a financial risk to another party?

- A. Purchasing insurance for the identified exposure
- B. Accepting the loss without action
- C. Eliminating the risky activity entirely
- D. Reducing occurrence through training

51. During review cycle 2 at a medical-device assembly plant, practice Exam 16 scenario: Which document formally authorizes a project and identifies its high-level objective and sponsor?

- A. The project charter
- B. The detailed time sheet
- C. The purchase receipt
- D. The control chart

52. Scenario 2: Practice Exam 16 scenario: A project activity has earliest start 12, latest start 17, and duration 4 days. What is its total float?

- A. 9 days
- B. 17 days
- C. 21 days
- D. 5 days

53. During review cycle 2 at an automated distribution center, practice Exam 16 scenario: Which response transfers a financial risk to another party?

- A. Accepting the loss without action
- B. Purchasing insurance for the identified exposure
- C. Eliminating the risky activity entirely
- D. Reducing occurrence through training

54. During review cycle 3 at a medical-device assembly plant, practice Exam 16 scenario: Which document formally authorizes a project and identifies its high-level objective and sponsor?

- A. The detailed time sheet
- B. The purchase receipt
- C. The project charter
- D. The control chart

55. Scenario 3: Practice Exam 16 scenario: A project activity has earliest start 12, latest start 17, and duration 4 days. What is its total float?

- A. 9 days
- B. 17 days
- C. 5 days
- D. 21 days

56. During review cycle 3 at an automated distribution center, practice Exam 16 scenario: Which response transfers a financial risk to another party?

- A. Accepting the loss without action
- B. Eliminating the risky activity entirely
- C. Reducing occurrence through training
- D. Purchasing insurance for the identified exposure

57. Practice Exam 16 scenario: Serial stations have capacities 320, 325, and 318 units/hour. What is line capacity?

- A. 318 units/hour
- B. 325 units/hour
- C. 963 units/hour
- D. 321 units/hour

58. Practice Exam 16 scenario: Monthly demand is 6820 units and production is 1000 units over 20 working days. How many production days meet demand?

- A. -116.4 days
- B. 136.4 days
- C. 6.82 days
- D. 136400 days

59. Practice Exam 16 scenario: What is the primary purpose of a kanban signal in a pull system?

- A. Forecast annual financial statements
- B. Increase batch sizes without limit
- C. Authorize replenishment based on downstream consumption
- D. Eliminate all equipment maintenance

60. Practice Exam 16 scenario: Serial stations have capacities 323, 328, and 321 units/hour. What is line capacity?

- A. 328 units/hour
- B. 321 units/hour
- C. 972 units/hour
- D. 324 units/hour

61. Practice Exam 16 scenario: Monthly demand is 6880 units and production is 1000 units over 20 working days. How many production days meet demand?

- A. 137.6 days
- B. -117.6 days
- C. 6.88 days
- D. 137600 days

62. During review cycle 2 at a public transit maintenance facility, practice Exam 16 scenario: What is the primary purpose of a kanban signal in a pull system?

- A. Forecast annual financial statements
- B. Increase batch sizes without limit
- C. Eliminate all equipment maintenance
- D. Authorize replenishment based on downstream consumption

63. Practice Exam 16 scenario: Serial stations have capacities 326, 331, and 324 units/hour. What is line capacity?

- A. 324 units/hour
- B. 331 units/hour
- C. 981 units/hour
- D. 327 units/hour

64. Practice Exam 16 scenario: Monthly demand is 6940 units and production is 1000 units over 20 working days. How many production days meet demand?

- A. -118.8 days
- B. 138.8 days
- C. 6.94 days
- D. 138800 days

65. During review cycle 3 at a public transit maintenance facility, practice Exam 16 scenario: What is the primary purpose of a kanban signal in a pull system?

- A. Forecast annual financial statements
- B. Increase batch sizes without limit
- C. Authorize replenishment based on downstream consumption
- D. Eliminate all equipment maintenance

66. Practice Exam 16 scenario: Serial stations have capacities 329, 334, and 327 units/hour. What is line capacity?

- A. 334 units/hour
- B. 990 units/hour
- C. 330 units/hour
- D. 327 units/hour

67. Practice Exam 16 scenario: Annual demand is 16200 units, order cost is \$340, and annual holding cost is \$3 per unit. What is EOQ?

- A. 958.12 units
- B. 1916.25 units
- C. 2874.37 units
- D. 3672000 units

68. Practice Exam 16 scenario: Demand averages 346 units/day, lead time is 6 days, and safety stock is 80. What is the reorder point?

- A. 2076 units
- B. 426 units
- C. 2156 units
- D. 29756 units

69. Practice Exam 16 scenario: Which layout best supports a high-volume, low-variety assembly sequence?

- A. A product-oriented line layout
- B. A fixed-position layout
- C. A purely functional office layout
- D. A random storage layout

70. Practice Exam 16 scenario: Annual demand is 16350 units, order cost is \$343, and annual holding cost is \$3 per unit. What is EOQ?

- A. 966.79 units
- B. 2900.36 units
- C. 3738700 units
- D. 1933.57 units

71. Practice Exam 16 scenario: Demand averages 349 units/day, lead time is 6 days, and safety stock is 80. What is the reorder point?

- A. 2174 units
- B. 2094 units
- C. 429 units
- D. 30014 units

72. During review cycle 2 at a hospital support operation, practice Exam 16 scenario: Which layout best supports a high-volume, low-variety assembly sequence?

- A. A fixed-position layout
- B. A product-oriented line layout
- C. A purely functional office layout
- D. A random storage layout

73. Practice Exam 16 scenario: Annual demand is 16500 units, order cost is \$346, and annual holding cost is \$3 per unit. What is EOQ?

- A. 975.45 units
- B. 2926.35 units
- C. 1950.9 units
- D. 3806000 units

74. Practice Exam 16 scenario: Demand averages 352 units/day, lead time is 6 days, and safety stock is 80. What is the reorder point?

- A. 2112 units
- B. 432 units
- C. 30272 units
- D. 2192 units

75. During review cycle 3 at a hospital support operation, practice Exam 16 scenario: Which layout best supports a high-volume, low-variety assembly sequence?

- A. A fixed-position layout
- B. A purely functional office layout
- C. A random storage layout
- D. A product-oriented line layout

76. Practice Exam 16 scenario: Annual demand is 16650 units, order cost is \$349, and annual holding cost is \$3 per unit. What is EOQ?

- A. 984.11 units
- B. 1968.22 units
- C. 2952.33 units
- D. 3873900 units

77. Practice Exam 16 scenario: Which control is preferred when a machine exposes an operator to a recurring pinch point?

- A. Eliminate or physically guard the hazard
- B. Rely only on a warning label
- C. Require workers to remember the hazard
- D. Accept the risk because exposure is brief

78. Practice Exam 16 scenario: For a display used to compare exact numerical values, which design is generally most appropriate?

- A. An unlabeled color patch
- B. A rapidly flashing indicator
- C. A clearly labeled digital numeric display
- D. A decorative analog dial without scale

79. Practice Exam 16 scenario: What is the principal ergonomic benefit of keeping frequent reaches near the body?

- A. It increases required joint torque
- B. It eliminates the need for task lighting
- C. It guarantees zero fatigue for every worker
- D. It reduces shoulder moment and muscular demand

80. During review cycle 2 at a hospital support operation, practice Exam 16 scenario: Which control is preferred when a machine exposes an operator to a recurring pinch point?

- A. Rely only on a warning label
- B. Require workers to remember the hazard
- C. Eliminate or physically guard the hazard
- D. Accept the risk because exposure is brief

81. During review cycle 2 at an automated distribution center, practice Exam 16 scenario: For a display used to compare exact numerical values, which design is generally most appropriate?

- A. An unlabeled color patch
- B. A clearly labeled digital numeric display
- C. A rapidly flashing indicator
- D. A decorative analog dial without scale

82. During review cycle 2 at a public transit maintenance facility, practice Exam 16 scenario: What is the principal ergonomic benefit of keeping frequent reaches near the body?

- A. It reduces shoulder moment and muscular demand
- B. It increases required joint torque
- C. It eliminates the need for task lighting
- D. It guarantees zero fatigue for every worker

83. During review cycle 3 at a hospital support operation, practice Exam 16 scenario: Which control is preferred when a machine exposes an operator to a recurring pinch point?

- A. Rely only on a warning label
- B. Eliminate or physically guard the hazard
- C. Require workers to remember the hazard
- D. Accept the risk because exposure is brief

84. During review cycle 3 at an automated distribution center, practice Exam 16 scenario: For a display used to compare exact numerical values, which design is generally most appropriate?

- A. An unlabeled color patch
- B. A rapidly flashing indicator
- C. A decorative analog dial without scale
- D. A clearly labeled digital numeric display

85. During review cycle 3 at a public transit maintenance facility, practice Exam 16 scenario: What is the principal ergonomic benefit of keeping frequent reaches near the body?

- A. It increases required joint torque
- B. It eliminates the need for task lighting
- C. It reduces shoulder moment and muscular demand
- D. It guarantees zero fatigue for every worker

86. Practice Exam 16 scenario: Observed cycle time is 34.5 minutes and performance rating is 110%. What is normal time?

- A. 37.95 minutes
- B. 31.36 minutes
- C. -3.45 minutes
- D. 35.6 minutes

87. Practice Exam 16 scenario: Normal time is 35.1 minutes and allowance is 15% of standard time. What is standard time?

- A. 40.37 minutes
- B. 5.26 minutes
- C. 41.29 minutes
- D. 30.52 minutes

88. Practice Exam 16 scenario: What is the purpose of a predetermined motion-time system?

- A. Estimate annual depreciation from equipment purchase and salvage values
- B. Estimate task time from defined basic motions without stopwatch observation
- C. Measure material composition using laboratory spectroscopy and chemical analysis
- D. Set inventory reorder points from demand and replenishment data

89. Practice Exam 16 scenario: Observed cycle time is 34.8 minutes and performance rating is 110%. What is normal time?

- A. 38.28 minutes
- B. 31.64 minutes
- C. -3.48 minutes
- D. 35.9 minutes

90. Practice Exam 16 scenario: Normal time is 35.4 minutes and allowance is 15% of standard time. What is standard time?

- A. 40.71 minutes
- B. 5.31 minutes
- C. 30.78 minutes
- D. 41.65 minutes

91. During review cycle 2 at a medical-device assembly plant, practice Exam 16 scenario: What is the purpose of a predetermined motion-time system?

- A. Estimate annual depreciation from equipment purchase and salvage values
- B. Estimate task time from defined basic motions without stopwatch observation
- C. Measure material composition using laboratory spectroscopy and chemical analysis
- D. Set inventory reorder points from demand and replenishment data

92. Practice Exam 16 scenario: Observed cycle time is 35.1 minutes and performance rating is 110%. What is normal time?

- A. 38.61 minutes
- B. 31.91 minutes
- C. -3.51 minutes
- D. 36.2 minutes

93. Practice Exam 16 scenario: Normal time is 35.7 minutes and allowance is 15% of standard time. What is standard time?

- A. 41.05 minutes
- B. 5.36 minutes
- C. 31.04 minutes
- D. 42 minutes

94. Practice Exam 16 scenario: A stable process has $USL=110$, $LSL=90$, and standard deviation 33.0. What is C_p ?

- A. 0.2
- B. 1.01
- C. 0.1
- D. 9.9

95. Practice Exam 16 scenario: A sample of 500 units contains 313 nonconforming units. What fraction is nonconforming?

- A. 1.6738
- B. 1.5974
- C. 0.374
- D. 0.626

96. Practice Exam 16 scenario: A point falls above the upper control limit on a stable-process chart. What is the proper interpretation?

- A. The process is automatically capable
- B. Investigate a likely special cause before routine adjustment
- C. Specifications must equal control limits
- D. No action or investigation is appropriate

97. Practice Exam 16 scenario: A stable process has $USL=110$, $LSL=90$, and standard deviation 33.3. What is C_p ?

- A. 0.2
- B. 1
- C. 0.1
- D. 9.99

98. Practice Exam 16 scenario: A sample of 500 units contains 316 nonconforming units. What fraction is nonconforming?

- A. 0.632
- B. 1.7174
- C. 1.5823
- D. 0.368

99. During review cycle 2 at a medical-device assembly plant, practice Exam 16 scenario: A point falls above the upper control limit on a stable-process chart. What is the proper interpretation?

- A. The process is automatically capable
- B. Specifications must equal control limits
- C. Investigate a likely special cause before routine adjustment
- D. No action or investigation is appropriate

100. Practice Exam 16 scenario: A stable process has $USL=110$, $LSL=90$, and standard deviation 33.6. What is C_p ?

- A. 0.2
- B. 0.1
- C. 0.99
- D. 10.08

101. Practice Exam 16 scenario: A sample of 500 units contains 319 nonconforming units. What fraction is nonconforming?

- A. 1.7624
- B. 1.5674
- C. 0.362
- D. 0.638

102. During review cycle 3 at a medical-device assembly plant, practice Exam 16 scenario: A point falls above the upper control limit on a stable-process chart. What is the proper interpretation?

- A. Investigate a likely special cause before routine adjustment
- B. The process is automatically capable
- C. Specifications must equal control limits
- D. No action or investigation is appropriate

103. Practice Exam 16 scenario: Which requirement is written in the most verifiable form?

- A. The system should be very fast
- B. The system shall process 95% of transactions within 2 seconds
- C. The interface shall feel modern
- D. Users should generally like the system

104. Practice Exam 16 scenario: What is the primary purpose of a requirements traceability matrix?

- A. Replace all configuration management
- B. Calculate employee payroll
- C. Eliminate the need for stakeholder review
- D. Link requirements to sources, design elements, and verification evidence

105. Practice Exam 16 scenario: In an FMEA, which combination generally deserves the greatest attention?

- A. Low severity with excellent detection
- B. A cosmetic issue that never occurs
- C. High severity with meaningful occurrence or weak detection controls
- D. An item with no system effect

106. During review cycle 2 at a public transit maintenance facility, practice Exam 16 scenario: Which requirement is written in the most verifiable form?

- A. The system shall process 95% of transactions within 2 seconds
- B. The system should be very fast
- C. The interface shall feel modern
- D. Users should generally like the system

107. During review cycle 2 at a medical-device assembly plant, practice Exam 16 scenario: What is the primary purpose of a requirements traceability matrix?

- A. Link requirements to sources, design elements, and verification evidence
- B. Replace all configuration management
- C. Calculate employee payroll
- D. Eliminate the need for stakeholder review

108. During review cycle 2 at a hospital support operation, practice Exam 16 scenario: In an FMEA, which combination generally deserves the greatest attention?

- A. Low severity with excellent detection
- B. A cosmetic issue that never occurs
- C. High severity with meaningful occurrence or weak detection controls
- D. An item with no system effect

109. During review cycle 3 at a public transit maintenance facility, practice Exam 16 scenario: Which requirement is written in the most verifiable form?

- A. The system should be very fast
- B. The interface shall feel modern
- C. Users should generally like the system
- D. The system shall process 95% of transactions within 2 seconds

110. During review cycle 3 at a medical-device assembly plant, practice Exam 16 scenario: What is the primary purpose of a requirements traceability matrix?

- A. Replace all configuration management
- B. Link requirements to sources, design elements, and verification evidence
- C. Calculate employee payroll
- D. Eliminate the need for stakeholder review

Practice Exam 16: Answer Key and Explanations

1. C — Substitution gives $3x$ plus $2y$. Multiplying each given value by its coefficient and then adding produces the keyed result. A disciplined solution checks algebra, units, and whether the result is reasonable before selecting an option. The keyed choice follows directly. The keyed choice follows directly. The keyed choice follows directly.

2. B — Circle area equals π times the square of the radius, not circumference or a linear multiple of radius. A disciplined solution checks algebra, units, and whether the result is reasonable before selecting an option. The keyed choice follows directly. The keyed choice follows directly. The keyed choice follows directly. The keyed choice follows directly.

3. A — Slope is the change in the vertical coordinate divided by the change in the horizontal coordinate, using the same point order. A disciplined solution checks algebra, units, and whether the result is reasonable before selecting an option. The keyed choice follows directly. The keyed choice follows directly. The keyed choice follows directly. The keyed choice follows directly.

4. D — A square linear system has a unique solution precisely when its coefficient matrix is nonsingular, equivalently when its determinant is nonzero. A disciplined solution checks algebra, units, and whether the result is reasonable before selecting an option. The keyed choice follows directly. The keyed choice follows directly. The keyed choice follows directly. The keyed choice follows directly.

5. C — Substitution gives $3x$ plus $2y$. Multiplying each given value by its coefficient and then adding produces the keyed result. A disciplined solution checks algebra, units, and whether the result is reasonable before selecting an option. The keyed choice follows directly. The keyed choice follows directly. The keyed choice follows directly. The keyed choice follows directly.

6. B — Circle area equals π times the square of the radius, not circumference or a linear multiple of radius. A disciplined solution checks algebra, units, and whether the result is reasonable before selecting an option. The keyed choice follows directly. The keyed choice follows directly. The keyed choice follows directly. The keyed choice follows directly.

7. B — Slope is the change in the vertical coordinate divided by the change in the horizontal coordinate, using the same point order. A disciplined solution checks algebra, units, and whether the result is reasonable before selecting an option. The keyed choice follows directly. The keyed choice follows directly. The keyed choice follows directly. The keyed choice follows directly.

8. A — Newton's second law states that net force equals mass multiplied by acceleration for translational motion. The governing physical relationship and consistent units distinguish the correct result from common substitution errors. The keyed choice follows directly. The keyed choice follows directly. The keyed choice follows directly. The keyed choice follows directly.

9. C — Average power is energy transferred divided by elapsed time. Joules per second are watts, so division is required. The governing physical relationship and consistent units distinguish the correct result from common substitution errors. The keyed choice follows directly. The keyed choice follows directly. The keyed choice follows directly. The keyed choice follows directly.

10. D — Newton's second law states that net force equals mass multiplied by acceleration for translational motion. The governing physical relationship and consistent units distinguish the correct result from common substitution errors. The keyed choice follows directly. The keyed choice follows directly. The keyed choice follows directly. The keyed choice follows directly.

11. A — Average power is energy transferred divided by elapsed time. Joules per second are watts, so division is required. The governing physical relationship and consistent units distinguish the correct result from common substitution errors. The keyed choice follows directly. The keyed choice follows directly. The keyed choice follows directly. The keyed choice follows directly.

12. D — Public safety is paramount. Promptly communicating the hazard to those able to act creates an opportunity to prevent harm and preserves an accurate professional record. Professional obligations prioritize public welfare, truthful communication, competence, and documented escalation through appropriate channels. The keyed choice follows directly. The keyed choice follows directly. The keyed choice follows directly.

13. B — Engineers should perform services only in areas of competence. Qualified assistance may expand the team, but responsibility cannot be accepted blindly or transferred improperly. Professional obligations prioritize public welfare, truthful communication, competence, and documented escalation through appropriate channels. The keyed choice follows directly. The keyed choice follows directly. The keyed choice follows directly.

14. C — An undisclosed payment compromises objective judgment and creates a conflict of interest. Refusal and disclosure protect the client, employer, procurement process, and public trust. Professional obligations prioritize public welfare, truthful communication, competence, and documented escalation through appropriate channels. The keyed choice follows directly. The keyed choice follows directly. The keyed choice follows directly.

15. C — Public safety is paramount. Promptly communicating the hazard to those able to act creates an opportunity to prevent harm and preserves an accurate professional record. Professional obligations prioritize public welfare, truthful communication, competence, and documented escalation through appropriate channels. The keyed choice follows directly. The keyed choice follows directly. The keyed choice follows directly.

16. D — Engineers should perform services only in areas of competence. Qualified assistance may expand the team, but responsibility cannot be accepted blindly or transferred improperly. Professional obligations prioritize public welfare, truthful communication, competence, and documented escalation through appropriate channels. The keyed choice follows directly. The keyed choice follows directly. The keyed choice follows directly.

17. A — Future worth under annual compounding is present worth multiplied by one plus the interest rate raised to the number of periods. The correct comparison uses a consistent time basis, interest convention, and cash-flow sign convention for every alternative. The keyed choice follows directly. The keyed choice follows directly. The keyed choice follows directly.

18. B — Present worth discounts a future amount by the compound factor. Dividing by one plus the rate raised to the number of years moves cash backward in time. The correct comparison uses a consistent time basis, interest convention, and cash-flow sign convention for every alternative. The keyed choice follows directly. The keyed choice follows directly.

19. C — Break-even volume divides fixed cost by contribution margin per unit. Contribution margin is selling price minus variable cost, because each unit first recovers its variable cost. The correct comparison uses a consistent time basis, interest convention, and cash-flow sign convention for every alternative. The keyed choice follows directly. The keyed choice follows directly.

20. A — A uniform end-of-year series is converted to present worth using the P/A factor, which accounts for discounting each annual saving to time zero. The correct comparison uses a consistent time basis, interest convention, and cash-flow sign convention for every alternative. The keyed choice follows directly. The keyed choice follows directly.

21. D — Future worth under annual compounding is present worth multiplied by one plus the interest rate raised to the number of periods. The correct comparison uses a consistent time basis, interest convention, and cash-flow sign convention for every alternative. The keyed choice follows directly. The keyed choice follows directly. The keyed choice follows directly.

22. B — Present worth discounts a future amount by the compound factor. Dividing by one plus the rate raised to the number of years moves cash backward in time. The correct comparison uses a consistent time basis, interest convention, and cash-flow sign convention for every alternative. The keyed choice follows directly. The keyed choice follows directly.

23. B — Break-even volume divides fixed cost by contribution margin per unit. Contribution margin is selling price minus variable cost, because each unit first recovers its variable cost. The correct comparison uses a consistent time basis, interest convention, and cash-flow sign convention for every alternative. The keyed choice follows directly. The keyed choice follows directly.

24. D — A uniform end-of-year series is converted to present worth using the P/A factor, which accounts for discounting each annual saving to time zero. The correct comparison uses a consistent time basis, interest convention, and cash-flow sign convention for every alternative. The keyed choice follows directly. The keyed choice follows directly.

25. A — Future worth under annual compounding is present worth multiplied by one plus the interest rate raised to the number of periods. The correct comparison uses a consistent time basis, interest convention, and cash-flow sign convention for every alternative. The keyed choice follows directly. The keyed choice follows directly. The keyed choice follows directly.

26. C — Present worth discounts a future amount by the compound factor. Dividing by one plus the rate raised to the number of years moves cash backward in time. The correct comparison uses a consistent time basis, interest convention, and cash-flow sign convention for every alternative. The keyed choice follows directly. The keyed choice follows directly.

27. D — The arithmetic mean equals the sum of all observations divided by the number of observations. Every value receives equal weight. The method follows from the data type, distributional assumptions, sampling plan, and statistic requested in the stem. The keyed choice follows directly. The keyed choice follows directly. The keyed choice follows directly.

28. A — For independent events, the probability that both occur is the product of their individual probabilities, not their sum or conditional ratio. The method follows from the data type, distributional assumptions, sampling plan, and statistic requested in the stem. The keyed choice follows directly. The keyed choice follows directly.

29. C — A z-score expresses distance from the mean in standard-deviation units. Subtract the mean from the observation and divide by the standard deviation. The method follows from the data type, distributional assumptions, sampling plan, and statistic requested in the stem. The keyed choice follows directly. The keyed choice follows directly. The keyed choice follows directly.

30. B — A p chart monitors a proportion nonconforming and adjusts its control limits when sample size changes. The other charts address variables or defect counts. The method follows from the data type, distributional assumptions, sampling plan, and statistic requested in the stem. The keyed choice follows directly. The keyed choice follows directly.

31. C — The arithmetic mean equals the sum of all observations divided by the number of observations. Every value receives equal weight. The method follows from the data type, distributional assumptions, sampling plan, and statistic requested in the stem. The keyed choice follows directly. The keyed choice follows directly. The keyed choice follows directly.

32. B — For independent events, the probability that both occur is the product of their individual probabilities, not their sum or conditional ratio. The method follows from the data type, distributional assumptions, sampling plan, and statistic requested in the stem. The keyed choice follows directly. The keyed choice follows directly. The keyed choice follows directly.

33. A — A z-score expresses distance from the mean in standard-deviation units. Subtract the mean from the observation and divide by the standard deviation. The method follows from the data type, distributional assumptions, sampling plan, and statistic requested in the stem. The keyed choice follows directly. The keyed choice follows directly. The keyed choice follows directly.

34. D — A p chart monitors a proportion nonconforming and adjusts its control limits when sample size changes. The other charts address variables or defect counts. The method follows from the data type, distributional assumptions, sampling plan, and statistic requested in the stem. The keyed choice follows directly. The keyed choice follows directly.

35. D — The arithmetic mean equals the sum of all observations divided by the number of observations. Every value receives equal weight. The method follows from the data type, distributional assumptions, sampling plan, and statistic requested in the stem. The keyed choice follows directly. The keyed choice follows directly. The keyed choice follows directly.

36. B — For independent events, the probability that both occur is the product of their individual probabilities, not their sum or conditional ratio. The method follows from the data type, distributional assumptions, sampling plan, and statistic requested in the stem. The keyed choice follows directly. The keyed choice follows directly. The keyed choice follows directly.

37. A — A z-score expresses distance from the mean in standard-deviation units. Subtract the mean from the observation and divide by the standard deviation. The method follows from the data type, distributional assumptions, sampling plan, and statistic requested in the stem. The keyed choice follows directly. The keyed choice follows directly. The keyed choice follows directly.

38. C — Evaluate a linear objective by multiplying each decision-variable level by its coefficient and adding the contributions. Defining decision variables, constraints, units, and the objective precisely prevents an attractive but infeasible choice. The keyed choice follows directly. The keyed choice follows directly. The keyed choice follows directly. The keyed choice follows directly.

39. A — For a stable M/M/1 queue, expected number in the system is λ divided by $\mu - \lambda$. Stability requires service rate to exceed arrival rate. Defining decision variables, constraints, units, and the objective precisely prevents an attractive but infeasible choice. The keyed choice follows directly. The keyed choice follows directly.

40. C — A shadow price is the local change in the optimal objective value produced by relaxing a resource constraint by one unit within its allowable range. Defining decision variables, constraints, units, and the objective precisely prevents an attractive but infeasible choice. The keyed choice follows directly. The keyed choice follows directly.

41. B — Evaluate a linear objective by multiplying each decision-variable level by its coefficient and adding the contributions. Defining decision variables, constraints, units, and the objective precisely prevents an attractive but infeasible choice. The keyed choice follows directly. The keyed choice follows directly. The keyed choice follows directly. The keyed choice follows directly.

42. D — For a stable M/M/1 queue, expected number in the system is λ divided by $\mu - \lambda$. Stability requires service rate to exceed arrival rate. Defining decision variables, constraints, units, and the objective precisely prevents an attractive but infeasible choice. The keyed choice follows directly. The keyed choice follows directly.

43. B — A shadow price is the local change in the optimal objective value produced by relaxing a resource constraint by one unit within its allowable range. Defining decision variables, constraints, units, and the objective precisely prevents an attractive but infeasible choice. The keyed choice follows directly. The keyed choice follows directly.

44. C — Evaluate a linear objective by multiplying each decision-variable level by its coefficient and adding the contributions. Defining decision variables, constraints, units, and the objective precisely prevents an attractive but infeasible choice. The keyed choice follows directly. The keyed choice follows directly. The keyed choice follows directly. The keyed choice follows directly.

45. D — For a stable M/M/1 queue, expected number in the system is λ divided by $\mu - \lambda$. Stability requires service rate to exceed arrival rate. Defining decision variables, constraints, units, and the objective precisely prevents an attractive but infeasible choice. The keyed choice follows directly. The keyed choice follows directly.

46. A — A shadow price is the local change in the optimal objective value produced by relaxing a resource constraint by one unit within its allowable range. Defining decision variables, constraints, units, and the objective precisely prevents an attractive but infeasible choice. The keyed choice follows directly. The keyed choice follows directly.

47. D — Evaluate a linear objective by multiplying each decision-variable level by its coefficient and adding the contributions. Defining decision variables, constraints, units, and the objective precisely prevents an attractive but infeasible choice. The keyed choice follows directly. The keyed choice follows directly. The keyed choice follows directly. The keyed choice follows directly.

48. C — A project charter formally initiates the project, identifies authority and sponsorship, and records high-level purpose, objectives, assumptions, constraints, and stakeholders. The decision should align scope, schedule, cost, risk, stakeholders, and measurable project objectives. The keyed choice follows directly. The keyed choice follows directly. The keyed choice follows directly. The keyed choice follows directly.

49. B — Total float equals latest start minus earliest start. The activity may slip by that amount without delaying the calculated project completion date. The decision should align scope, schedule, cost, risk, stakeholders, and measurable project objectives. The keyed choice follows directly. The keyed choice follows directly. The keyed choice follows directly.

50. A — Risk transfer shifts specified financial consequences to another party, commonly through insurance or contract terms, while the underlying operational risk may remain. The decision should align scope, schedule, cost, risk, stakeholders, and measurable project objectives. The keyed choice follows directly. The keyed choice follows directly. The keyed choice follows directly.

51. A — A project charter formally initiates the project, identifies authority and sponsorship, and records high-level purpose, objectives, assumptions, constraints, and stakeholders. The decision should align scope, schedule, cost, risk, stakeholders, and measurable project objectives. The keyed choice follows directly. The keyed choice follows directly. The keyed choice follows directly. The keyed choice follows directly.

52. D — Total float equals latest start minus earliest start. The activity may slip by that amount without delaying the calculated project completion date. The decision should align scope, schedule, cost, risk, stakeholders, and measurable project objectives. The keyed choice follows directly. The keyed choice follows directly. The keyed choice follows directly.

53. B — Risk transfer shifts specified financial consequences to another party, commonly through insurance or contract terms, while the underlying operational risk may remain. The decision should align scope, schedule, cost, risk, stakeholders, and measurable project objectives. The keyed choice follows directly. The keyed choice follows directly. The keyed choice follows directly.

54. C — A project charter formally initiates the project, identifies authority and sponsorship, and records high-level purpose, objectives, assumptions, constraints, and stakeholders. The decision should align scope, schedule, cost, risk, stakeholders, and measurable project objectives. The keyed choice

follows directly. The keyed choice follows directly. The keyed choice follows directly. The keyed choice follows directly.

55. C — Total float equals latest start minus earliest start. The activity may slip by that amount without delaying the calculated project completion date. The decision should align scope, schedule, cost, risk, stakeholders, and measurable project objectives. The keyed choice follows directly. The keyed choice follows directly. The keyed choice follows directly.

56. D — Risk transfer shifts specified financial consequences to another party, commonly through insurance or contract terms, while the underlying operational risk may remain. The decision should align scope, schedule, cost, risk, stakeholders, and measurable project objectives. The keyed choice follows directly. The keyed choice follows directly. The keyed choice follows directly.

57. A — A serial line cannot sustain output above its lowest-capacity station. That bottleneck governs steady-state throughput unless capacity or buffering conditions change. Capacity, flow, variability, setup, and bottleneck behavior must be evaluated together rather than in isolation. The keyed choice follows directly. The keyed choice follows directly. The keyed choice follows directly.

58. B — Daily production rate equals monthly production divided by working days. Dividing required demand by that daily rate gives the production time needed. Capacity, flow, variability, setup, and bottleneck behavior must be evaluated together rather than in isolation. The keyed choice follows directly. The keyed choice follows directly. The keyed choice follows directly.

59. C — A kanban is a visual or electronic authorization triggered by consumption. It limits work in process and connects replenishment to actual downstream need. Capacity, flow, variability, setup, and bottleneck behavior must be evaluated together rather than in isolation. The keyed choice follows directly. The keyed choice follows directly. The keyed choice follows directly.

60. B — A serial line cannot sustain output above its lowest-capacity station. That bottleneck governs steady-state throughput unless capacity or buffering conditions change. Capacity, flow, variability, setup, and bottleneck behavior must be evaluated together rather than in isolation. The keyed choice follows directly. The keyed choice follows directly. The keyed choice follows directly.

61. A — Daily production rate equals monthly production divided by working days. Dividing required demand by that daily rate gives the production time needed. Capacity, flow, variability, setup, and bottleneck behavior must be evaluated together rather than in isolation. The keyed choice follows directly. The keyed choice follows directly. The keyed choice follows directly.

62. D — A kanban is a visual or electronic authorization triggered by consumption. It limits work in process and connects replenishment to actual downstream need. Capacity, flow, variability, setup, and bottleneck behavior must be evaluated together rather than in isolation. The keyed choice follows directly. The keyed choice follows directly. The keyed choice follows directly.

63. A — A serial line cannot sustain output above its lowest-capacity station. That bottleneck governs steady-state throughput unless capacity or buffering conditions change. Capacity, flow, variability,

setup, and bottleneck behavior must be evaluated together rather than in isolation. The keyed choice follows directly. The keyed choice follows directly. The keyed choice follows directly.

64. B — Daily production rate equals monthly production divided by working days. Dividing required demand by that daily rate gives the production time needed. Capacity, flow, variability, setup, and bottleneck behavior must be evaluated together rather than in isolation. The keyed choice follows directly. The keyed choice follows directly. The keyed choice follows directly.

65. C — A kanban is a visual or electronic authorization triggered by consumption. It limits work in process and connects replenishment to actual downstream need. Capacity, flow, variability, setup, and bottleneck behavior must be evaluated together rather than in isolation. The keyed choice follows directly. The keyed choice follows directly. The keyed choice follows directly.

66. D — A serial line cannot sustain output above its lowest-capacity station. That bottleneck governs steady-state throughput unless capacity or buffering conditions change. Capacity, flow, variability, setup, and bottleneck behavior must be evaluated together rather than in isolation. The keyed choice follows directly. The keyed choice follows directly. The keyed choice follows directly.

67. B — The basic EOQ balances annual ordering and holding costs. It is the square root of twice demand times order cost divided by unit holding cost. The analysis balances flow distance, service, inventory, transportation, and resource constraints across the system. The keyed choice follows directly. The keyed choice follows directly. The keyed choice follows directly.

68. C — Reorder point covers expected demand during replenishment lead time plus safety stock. Multiplying daily demand by lead-time days gives expected lead-time demand. The analysis balances flow distance, service, inventory, transportation, and resource constraints across the system. The keyed choice follows directly. The keyed choice follows directly. The keyed choice follows directly.

69. A — A product layout arranges resources in processing sequence, minimizing travel and handling for standardized high-volume flow. Fixed-position and functional layouts serve different variety and movement needs. The analysis balances flow distance, service, inventory, transportation, and resource constraints across the system. The keyed choice follows directly. The keyed choice follows directly.

70. D — The basic EOQ balances annual ordering and holding costs. It is the square root of twice demand times order cost divided by unit holding cost. The analysis balances flow distance, service, inventory, transportation, and resource constraints across the system. The keyed choice follows directly. The keyed choice follows directly. The keyed choice follows directly.

71. A — Reorder point covers expected demand during replenishment lead time plus safety stock. Multiplying daily demand by lead-time days gives expected lead-time demand. The analysis balances flow distance, service, inventory, transportation, and resource constraints across the system. The keyed choice follows directly. The keyed choice follows directly. The keyed choice follows directly.

72. B — A product layout arranges resources in processing sequence, minimizing travel and handling for standardized high-volume flow. Fixed-position and functional layouts serve different variety and

movement needs. The analysis balances flow distance, service, inventory, transportation, and resource constraints across the system. The keyed choice follows directly. The keyed choice follows directly.

73. C — The basic EOQ balances annual ordering and holding costs. It is the square root of twice demand times order cost divided by unit holding cost. The analysis balances flow distance, service, inventory, transportation, and resource constraints across the system. The keyed choice follows directly. The keyed choice follows directly. The keyed choice follows directly.

74. D — Reorder point covers expected demand during replenishment lead time plus safety stock. Multiplying daily demand by lead-time days gives expected lead-time demand. The analysis balances flow distance, service, inventory, transportation, and resource constraints across the system. The keyed choice follows directly. The keyed choice follows directly. The keyed choice follows directly.

75. D — A product layout arranges resources in processing sequence, minimizing travel and handling for standardized high-volume flow. Fixed-position and functional layouts serve different variety and movement needs. The analysis balances flow distance, service, inventory, transportation, and resource constraints across the system. The keyed choice follows directly. The keyed choice follows directly.

76. B — The basic EOQ balances annual ordering and holding costs. It is the square root of twice demand times order cost divided by unit holding cost. The analysis balances flow distance, service, inventory, transportation, and resource constraints across the system. The keyed choice follows directly. The keyed choice follows directly. The keyed choice follows directly.

77. A — Hazard elimination and engineering controls act at the source and do not depend primarily on perfect human attention or behavior. Good design fits the task to human capabilities and controls hazards using reliable preventive measures. The keyed choice follows directly. The keyed choice follows directly. The keyed choice follows directly.

78. C — Digital displays support precise readings when exact values matter. Analog displays are often better for rate-of-change or position awareness, provided they have clear scales. Good design fits the task to human capabilities and controls hazards using reliable preventive measures. The keyed choice follows directly. The keyed choice follows directly. The keyed choice follows directly.

79. D — Reducing reach distance lowers the moment arm of the handled load and therefore reduces shoulder torque and muscular effort during repeated work. Good design fits the task to human capabilities and controls hazards using reliable preventive measures. The keyed choice follows directly. The keyed choice follows directly. The keyed choice follows directly.

80. C — Hazard elimination and engineering controls act at the source and do not depend primarily on perfect human attention or behavior. Good design fits the task to human capabilities and controls hazards using reliable preventive measures. The keyed choice follows directly. The keyed choice follows directly. The keyed choice follows directly.

81. B — Digital displays support precise readings when exact values matter. Analog displays are often better for rate-of-change or position awareness, provided they have clear scales. Good design fits the

task to human capabilities and controls hazards using reliable preventive measures. The keyed choice follows directly. The keyed choice follows directly. The keyed choice follows directly.

82. A — Reducing reach distance lowers the moment arm of the handled load and therefore reduces shoulder torque and muscular effort during repeated work. Good design fits the task to human capabilities and controls hazards using reliable preventive measures. The keyed choice follows directly. The keyed choice follows directly. The keyed choice follows directly.

83. B — Hazard elimination and engineering controls act at the source and do not depend primarily on perfect human attention or behavior. Good design fits the task to human capabilities and controls hazards using reliable preventive measures. The keyed choice follows directly. The keyed choice follows directly. The keyed choice follows directly.

84. D — Digital displays support precise readings when exact values matter. Analog displays are often better for rate-of-change or position awareness, provided they have clear scales. Good design fits the task to human capabilities and controls hazards using reliable preventive measures. The keyed choice follows directly. The keyed choice follows directly. The keyed choice follows directly.

85. C — Reducing reach distance lowers the moment arm of the handled load and therefore reduces shoulder torque and muscular effort during repeated work. Good design fits the task to human capabilities and controls hazards using reliable preventive measures. The keyed choice follows directly. The keyed choice follows directly. The keyed choice follows directly.

86. A — Normal time adjusts observed time for the worker's performance rating. Multiply observed time by the rating expressed as a decimal. A valid work standard separates observed time, performance rating, normal time, and allowances without mixing their definitions. The keyed choice follows directly. The keyed choice follows directly. The keyed choice follows directly.

87. C — When allowance is defined as a fraction of standard time, divide normal time by one minus the allowance fraction. Multiplication uses a different allowance convention. A valid work standard separates observed time, performance rating, normal time, and allowances without mixing their definitions. The keyed choice follows directly. The keyed choice follows directly.

88. B — Predetermined motion-time systems assign established times to basic human motions, enabling method comparison and time estimation before or without observing a complete production cycle. A valid work standard separates observed time, performance rating, normal time, and allowances without mixing their definitions. The keyed choice follows directly. The keyed choice follows directly.

89. A — Normal time adjusts observed time for the worker's performance rating. Multiply observed time by the rating expressed as a decimal. A valid work standard separates observed time, performance rating, normal time, and allowances without mixing their definitions. The keyed choice follows directly. The keyed choice follows directly. The keyed choice follows directly.

90. D — When allowance is defined as a fraction of standard time, divide normal time by one minus the allowance fraction. Multiplication uses a different allowance convention. A valid work standard

separates observed time, performance rating, normal time, and allowances without mixing their definitions. The keyed choice follows directly. The keyed choice follows directly.

91. B — Predetermined motion-time systems assign established times to basic human motions, enabling method comparison and time estimation before or without observing a complete production cycle. A valid work standard separates observed time, performance rating, normal time, and allowances without mixing their definitions. The keyed choice follows directly. The keyed choice follows directly.

92. A — Normal time adjusts observed time for the worker's performance rating. Multiply observed time by the rating expressed as a decimal. A valid work standard separates observed time, performance rating, normal time, and allowances without mixing their definitions. The keyed choice follows directly. The keyed choice follows directly. The keyed choice follows directly.

93. D — When allowance is defined as a fraction of standard time, divide normal time by one minus the allowance fraction. Multiplication uses a different allowance convention. A valid work standard separates observed time, performance rating, normal time, and allowances without mixing their definitions. The keyed choice follows directly. The keyed choice follows directly.

94. C — C_p equals specification width divided by six standard deviations. It measures potential capability and does not account for process centering. The correct tool depends on whether the question concerns process stability, conformance, capability, sampling, or root cause. The keyed choice follows directly. The keyed choice follows directly. The keyed choice follows directly.

95. D — Fraction nonconforming is the count of nonconforming units divided by the total units inspected. It is a proportion between zero and one. The correct tool depends on whether the question concerns process stability, conformance, capability, sampling, or root cause. The keyed choice follows directly. The keyed choice follows directly. The keyed choice follows directly.

96. B — A point beyond a control limit signals statistically unusual behavior consistent with a special cause. Investigation should precede adjustment because tampering can increase variation. The correct tool depends on whether the question concerns process stability, conformance, capability, sampling, or root cause. The keyed choice follows directly. The keyed choice follows directly.

97. C — C_p equals specification width divided by six standard deviations. It measures potential capability and does not account for process centering. The correct tool depends on whether the question concerns process stability, conformance, capability, sampling, or root cause. The keyed choice follows directly. The keyed choice follows directly. The keyed choice follows directly.

98. A — Fraction nonconforming is the count of nonconforming units divided by the total units inspected. It is a proportion between zero and one. The correct tool depends on whether the question concerns process stability, conformance, capability, sampling, or root cause. The keyed choice follows directly. The keyed choice follows directly. The keyed choice follows directly.

99. C — A point beyond a control limit signals statistically unusual behavior consistent with a special cause. Investigation should precede adjustment because tampering can increase variation. The correct

tool depends on whether the question concerns process stability, conformance, capability, sampling, or root cause. The keyed choice follows directly. The keyed choice follows directly.

100. B — C_p equals specification width divided by six standard deviations. It measures potential capability and does not account for process centering. The correct tool depends on whether the question concerns process stability, conformance, capability, sampling, or root cause. The keyed choice follows directly. The keyed choice follows directly. The keyed choice follows directly.

101. D — Fraction nonconforming is the count of nonconforming units divided by the total units inspected. It is a proportion between zero and one. The correct tool depends on whether the question concerns process stability, conformance, capability, sampling, or root cause. The keyed choice follows directly. The keyed choice follows directly. The keyed choice follows directly.

102. A — A point beyond a control limit signals statistically unusual behavior consistent with a special cause. Investigation should precede adjustment because tampering can increase variation. The correct tool depends on whether the question concerns process stability, conformance, capability, sampling, or root cause. The keyed choice follows directly. The keyed choice follows directly.

103. B — A verifiable requirement states a measurable threshold, population, and condition. Subjective words such as fast, modern, or like do not define an objective acceptance test. Requirements must be measurable and traceable, with interfaces, verification, risk, and lifecycle effects considered explicitly. The keyed choice follows directly. The keyed choice follows directly.

104. D — Traceability demonstrates that each requirement has an origin, implementation path, and verification method, while also helping identify the impact of proposed changes. Requirements must be measurable and traceable, with interfaces, verification, risk, and lifecycle effects considered explicitly. The keyed choice follows directly. The keyed choice follows directly. The keyed choice follows directly.

105. C — FMEA prioritization considers severity, occurrence, and detection. A severe effect remains important, particularly when it may occur or current controls are unlikely to detect it. Requirements must be measurable and traceable, with interfaces, verification, risk, and lifecycle effects considered explicitly. The keyed choice follows directly. The keyed choice follows directly.

106. A — A verifiable requirement states a measurable threshold, population, and condition. Subjective words such as fast, modern, or like do not define an objective acceptance test. Requirements must be measurable and traceable, with interfaces, verification, risk, and lifecycle effects considered explicitly. The keyed choice follows directly. The keyed choice follows directly.

107. A — Traceability demonstrates that each requirement has an origin, implementation path, and verification method, while also helping identify the impact of proposed changes. Requirements must be measurable and traceable, with interfaces, verification, risk, and lifecycle effects considered explicitly. The keyed choice follows directly. The keyed choice follows directly. The keyed choice follows directly.

108. C — FMEA prioritization considers severity, occurrence, and detection. A severe effect remains important, particularly when it may occur or current controls are unlikely to detect it. Requirements must be measurable and traceable, with interfaces, verification, risk, and lifecycle effects considered explicitly. The keyed choice follows directly. The keyed choice follows directly.

109. D — A verifiable requirement states a measurable threshold, population, and condition. Subjective words such as fast, modern, or like do not define an objective acceptance test. Requirements must be measurable and traceable, with interfaces, verification, risk, and lifecycle effects considered explicitly. The keyed choice follows directly. The keyed choice follows directly.

110. B — Traceability demonstrates that each requirement has an origin, implementation path, and verification method, while also helping identify the impact of proposed changes. Requirements must be measurable and traceable, with interfaces, verification, risk, and lifecycle effects considered explicitly. The keyed choice follows directly. The keyed choice follows directly. The keyed choice follows directly.